

Color Invigorate

INNOTECH[®] COLOR INVIGORATE is a proprietary blend of water soluble cementitious and other coloring agents designed for the use in providing secondary color and/or highlighting to decorative stamped concrete, stampable overlay or any other concrete surface.

Product Features and Benefits

INNOTECH COLOR INVIGORATE ...

- Is easy to use, mixes with water.
- Can be applied in two easy methods: Pour out and broom in or spray apply with pump up sprayer.
- Contains zero VOC.
- Is available in 42 standard colors. Reference the INNOTECH COLOR HARDENER color chart for selections.
- Takes the headache out of applying secondary coloring to overlays.
- Requires no messy clean up.

Prior to Application

- Surface to be treated must be clean and free of any curing agents, sealers, dirt, dust, debris or other contaminants that may interfere with the proper adhesion of INNOTECH COLOR INVIGORATE.
- If INNOTECH COLOR INVIGORATE is to be applied to a non-textured surface, a minimal surface profiling is required to insure proper bonding to the non-textured surface. A profile equal to the ICRI CSP-1 profile is recommended.

Application Methods

- Soft flagged tip broom.
- Pump-up sprayer.

Mixing Instructions

- Pour one gallon of clean potable water into a clean five gallon bucket.
- Mix in 6 ounces of INNOTECH COLOR INVIGORATE into the water and mix thoroughly until product is completely dissolved.
- Add mixed product to pump up sprayer, if using spray applied method of application. Shake sprayer regularly to keep product suspended in water throughout application.

Product Application

Option #1

- Lightly pre-wet the surface to be treated with INNOTECH COLOR INVIGORATE with water to assist in the distribution of material.
- Apply INNOTECH COLOR INVIGORATE that has been mixed to entire surface as a color wash, using a flagged tipped broom to massage Color Invigorate into or out of the low lying areas as needed or desired.
- Should any brush marks remain after the initial application of Color Invigorate, immediately mist the surface with water and lightly broom to eliminate.

Option #2

- Lightly pre-wet the surface to be treated with INNOTECH COLOR INVIGORATE with water to assist in the distribution of material.
- Apply INNOTECH COLOR INVIGORATE to entire surface area with pump-up sprayer, highlighting areas as desired.
- Use a soft flagged tip broom to back brush or move applied product into or out of low lying areas as needed.
- Should any brush marks remain after the initial application of invigorate, immediately mist surface with water and lightly broom to eliminate.

Sealing INNOTECH Color Invigorate

- Allow 2-4 hours before sealing. With the use of a soft flag tipped broom, lightly broom area to remove any excess laitance that may be present.
- Seal using Innotech solvent based or water based sealers. Call Innotech at (877) 829-7880 for the sealer recommended to fit your needs.

Maintenance

- Proper sealer maintenance is crucial to the ultimate success of any decorative concrete project.
- Ensure that sealer is checked at regular intervals and reapplied as necessary.

Product Limitations

- Product should be applied when surface temperature is between 50-90 °F.
- Proper surface profiling is necessary for non-textured concrete surfaces. (See prior to application section)

Available Packaging and Coverage Information

Packaging: INNOTECH COLOR INVIGORATE is available in 1-gallon buckets, containing approximately 3 lbs. of powder.
Coverage: Approximately 2,000-3,000 sq. ft. per 3 lb. container.

Product Shelf Life/Storage

INNOTECH COLOR INVIGORATE should be stored indoors, away from heat or direct sunlight. Do not store below 40 °F. If the Liquid freezes, discard.
Shelf life: 24 months from date of manufacture in unopened, original container.

Product Handling


Prior to using INNOTECH COLOR INVIGORATE please reference the corresponding Material Safety Data Sheet to ensure safe handling.

Warranty:

INNOTECH COLOR INVIGORATE is a proprietary product, warranted to be of uniform quality within our stringent manufacturing tolerances. As no control is exercised over the product use, no warranty is made as to the effects of such use (neither expressed nor implied). Obligation of the seller and manufacturer under this warranty shall be limited to a refund of the purchase price of that portion of the material proven to be defective. The user assumes all other risk and liability resulting from uses of this product.

†PLEASE REFER TO CORRESPONDING TECHNICAL BULLETIN FOR PRODUCT AND APPLICATION DATA.

INNOTECH COLOR INVIGORATE and other INNOTECH products are for professional use only.

 Innotech Decorative Concrete Products is a member of the ChromaScape family of brands.
For more information, visit www.chromascape.com. ©2012 ChromaScape, Inc.

1.5M 08.12

INNOTECH products can be purchased at:



INNOTECH Decorative Concrete Products
Customer Service 877-829-7880 or 330-425-2506
Fax 330-425-2466
CustomerService@InnotechDCP.com
www.InnotechDCP.com