

Seal Strips

INNOTECH INTERIOR FLOOR STRIP (For removal of maintenance topcoat sealers)

INNOTECH INTERIOR FLOOR STRIP is a concentrated strip that quickly and effectively strips maintenance topcoat sealers such as INNOTECH INTERIOR FLOOR FINISH⁺ or INNOTECH NATURAL BEAUTY⁺ without harming or removing the base sealer.

INNOTECH SEAL STRIP (For removal of base sealers)

INNOTECH SEAL STRIP provides a user-safe and environmentally safe stripper for solvent-based and water-based sealers.

INNOTECH INTERIOR FLOOR STRIP

Product Features and Benefits

When used according to directions, INNOTECH INTERIOR FLOOR STRIP is safe to use on any surface that has been treated with a maintenance topcoat of INNOTECH INTERIOR FLOOR FINISH⁺ or INNOTECH NATURAL BEAUTY⁺.

Prior to Application

Dilution Ratios: For removal of INNOTECH INTERIOR FLOOR FINISH⁺ dilute INNOTECH INTERIOR FLOOR STRIP 6-parts product to 10-parts water. Dilution can range between 1:6 and 1:10 (depending on amount of sealer being removed).

- Prior to application, test INNOTECH INTERIOR FLOOR STRIP in an inconspicuous area to ensure compatibility. Contact an INNOTECH Representative with any questions about compatibility.

Product Application

- Apply with sprayer or mop.
- Allow the mixed solution to sit for 5-10 minutes, to dissolve and “raise” the maintenance topcoat to be removed (allow mixed solution to do the initial work).
- Light or medium scrub pads or brushes may be used. INNOTECH INTERIOR FLOOR STRIP works with low foaming and easy rinsing.
- After scrubbing, absorb excess solution and stripped sealer. Rinse surface and dry completely.

Product Limitations

- This product is intended to remove only INNOTECH INTERIOR FLOOR FINISH⁺ and INNOTECH NATURAL BEAUTY⁺, polymer surface finishes.
- This stripping product should not be used to strip any other INNOTECH Sealers.
- INNOTECH INTERIOR FLOOR STRIP is not intended for use as a general purpose cleaner.

Available Packaging and Coverage Information

Packaging: INNOTECH INTERIOR FLOOR STRIP is available in 1-gallon containers.

Coverage rates may vary depending on surface porosity, texture, age and condition of the concrete, the application method, and other local conditions: Approximately 1,000 s.f./gallon.

Applicable Standards

INNOTECH INTERIOR FLOOR STRIP complies with ASTM D 3209-82 for freeze/thaw stability for a minimum of three cycles.

Technical Information

Please refer to the corresponding MSDS for hazard-related information.

- Color/Odor Clear, yellow/Citrus
- Surface Tension 29 dynes per cm
- Detergent Type Nonionic
- Specific Gravity 1.03 (H₂O=1)
- Density..... 8.6 pounds per gallon
- Flash Point None
- Solubility in Water 100% for hard, soft and/or deionized water
- pH 13.8 + 0.2 concentrate, 12.9 + 0.2 for 1:10 dilution

INNOTECH SEAL STRIP

Product Features and Benefits

This product quickly and efficiently emulsifies and strips INNOTECH Solvent-Based and Water-Based sealers such as INNOTECH SOLVENT-BASED SEALERS⁺, INNOTECH PERMASEAL⁺ and INNOTECH CEMSEAL⁺.

Prior to Application

- Prior to application, test INNOTECH SEAL STRIP in an inconspicuous area to ensure compatibility.
- This product is safe to use on all colored or imprinted concrete. Contact an INNOTECH Representative with any questions about compatibility.
- INNOTECH SEAL STRIP is a water-dispersable. However, it is most effective when used undiluted. **Important:** Be careful not to walk on areas where INNOTECH SEAL STRIP is being applied as the product can be slippery underfoot. Wear slip-resistant footwear to walk in the application area.

Product Application

- Apply with mop or sprayer and work a small area at a time.
- Allow at least 15 minutes “dwell” time (depending on amount and type of coating to be stripped).
- Following “dwell” time, scrape or scrub surface with a floor buffer and a stripping brush or pad. Pick up or vacuum up the excess solution.
- Scrub surface with a mild alkaline detergent solution such as INNOTECH FLOOR CLEANER⁺ followed by a thorough rinsing.
- Allow surface to dry before applying seal or finish.

Product Limitations

- This product is not for use on resilient surfaces such as vinyl or vinyl composition tile.
- INNOTECH STRIP contains no methylene chloride nor is it flammable. This product does not produce carcinogen hazards associated with petroleum strippers.

Available Packaging and Coverage Information

Packaging:

- INNOTECH SEAL STRIP is available in 1- and 5-gallon containers.

Coverage rates may vary depending on surface porosity, texture, age and condition of the concrete, the application method, and other local conditions:

- Approximately 60-100 square feet per gallon (depending on amount and type of sealer being removed).

Applicable Standards

INNOTECH SEAL STRIP complies with ASTM D 3209-82 for freeze/thaw stability for a minimum of three cycles.

Technical Information

Please refer to the corresponding MSDS for hazard-related information.

- Color/Odor Light straw/Citrus
- Surface Tension 29 dynes per centimeter
- Detergent Type Nonionic
- Specific Gravity 0.97 (H₂O=1)
- Solubility in Water Miscible
- Density..... 8.1 pounds per gallon
- pH 8±0.5
- Flash Point 140 °F

Product Shelf Life/Storage

INNOTECH SEAL STRIPS listed in this document should be stored indoors, away from heat and direct sunlight. Do not allow products to freeze.

Shelf Life: 12 months

Product Handling

Prior to using any of the products listed above, please reference the corresponding Material Safety Data Sheet to ensure safe handling.

Product Warranty

These INNOTECH SEAL STRIPS are proprietary, warranted to be of uniform quality within our stringent manufacturing tolerances. As no control is exercised over the product use, no warranty is made as to the effects of such use (neither expressed or implied). Obligation of the seller and manufacturer under this warranty shall be limited to a refund of the purchase price of that portion of the material proven to be defective. The user assumes all other risk and liability resulting from uses of this product. Contact INNOTECH with any questions regarding this policy. *Innotech is a registered trademark of CHROMASYSTEMS LLC, an Ohio company.*

†PLEASE REFER TO THE CORRESPONDING TECHNICAL BULLETIN FOR PRODUCT AND APPLICATION DATA.

INNOTECH CLEANERS and other INNOTECH products are for professional use only.

Innotech Decorative Concrete Products is a registered trademark of ChromaSystems LLC, a wholly owned part of the ChromaScape family of companies.

For more information, go to www.chromascape.com. ©2010 CHROMASYSTEMS, LLC. Printed in U.S.A.

2M

01.10

INNOTECH products can be purchased at:



INNOTECH Decorative Concrete Products
2055 Enterprise Parkway • Twinsburg, OH 44087
Customer Service 877-829-7880 or 330-425-2506
Fax 330-425-2466
www.innotechdcp.com