

Select-Etch

INNOTECH SELECT-ETCH is a water-based, sprayable top-surface deactivator which does not require covering with plastic for protection. INNOTECH SELECT-ETCH is designed to stop the hydration of the cement to a specific depth of your choosing on freshly poured concrete. INNOTECH SELECT-ETCH is formulated in multiple depths of etch, each depth is number/color coded for ease of use and safety.

Product Features and Benefits

INNOTECH SELECT-ETCH ...

- Multiple depths of etch available.
- Exceptional depth of etch control.
- Consistent finish.
- Color/number coded for easy identification of depth control.
- No plastic covering required.
- Rain and wind resistant.
- Quick turnaround.

Concrete Mix Design

INNOTECH SELECT-ETCH is designed for a standard 6-sack mix. A sample should be made under jobsite conditions to ensure final results.

Prior to Application

- Protect all surrounding or adjacent areas from overspray or splatter that are not intended to receive INNOTECH SELECT-ETCH.
- Place concrete and float or trowel finish insuring that all surface bleed water has evaporated prior to applying INNOTECH SELECT-ETCH.

Product Application

- Apply immediately after bleed water has evaporated.
- INNOTECH SELECT-ETCH should be applied with a low pressure sprayer evenly across the entire area to be treated.
- Care should be taken to ensure complete and even coverage. There is no need to cover with plastic sheeting as INNOTECH SELECT-ETCH is rain and wind resistant.
- Do not over-apply and do not allow puddles to form.

Removal

Environmental conditions, as well as mix design, may affect the performance of INNOTECH SELECT-ETCH. Under normal conditions utilizing a standard 6-sack mix design, the surface can be exposed after 14+ hours. INNOTECH SELECT-ETCH is normally washed away the next day. INNOTECH SELECT-ETCH can be removed with the use of a pressure washer or a hose with an appropriate spray tip/nozzle and the use of a stiff deck brush.

Sealing Concrete That Has Been Treated With INNOTECH Select-Etch

Concrete that has been treated with INNOTECH SELECT-ETCH can be sealed with an appropriate INNOTECH SEALER once the concrete has sufficiently cured. Innotech offers both Solvent-Based as well as Water-Based sealers to meet nationwide VOC regulations.

- Contact Innotech at 877-829-7880 for the appropriate sealer for your specific needs and location.

Technical Information

VOC: <100 g/l

Flash Point: N/A

Meets ASTM C 309 when left in place for 28 days prior to removal.

HMS: Health=1 Flammability=0, Reactivity=1 Protection=B

Always wear eye protection, rubber gloves, and paper mask.

Maintenance

- Proper sealer maintenance is crucial to the ultimate success of any decorative concrete project.
- Keep concrete clean by washing surface with a Ph neutral cleaner and reseal as necessary.

Product Limitations

INNOTECH SELECT-ETCH is to be applied to horizontal surfaces only. For vertical surface applications, contact Innotech at 877-829-7880.

Available Packaging and Coverage Information

Packaging: INNOTECH SELECT-ETCH is available in 5-gallon pails.

Coverage rates may vary depending on the texture, porosity and condition of the concrete, application method, and other local conditions.

Coverage: INNOTECH SELECT-ETCH should be applied at approximately 200 square feet per gallon. INNOTECH SELECT-ETCH must be applied to entire surface area that is being treated.

Description / Number # / Color

Description	Number #	Color
Acid Etch	03	Violet
Sandblast Etch	05	Sky Blue
Up to 1/4" Aggregate	15	Yellow
1/8" to 3/8" Aggregate	50	Pea Green
3/8" to 1/2" Aggregate	100	Gray

Product Shelf Life/Storage

INNOTECH SELECT-ETCH should be stored in dry conditions. Do not allow product to freeze.
Shelf life: One year from date of manufacture in unopened, original container.

Product Handling

Prior to using INNOTECH SELECT-ETCH please reference the corresponding Safety Data Sheet to ensure safe handling. Always wear gloves and eye protection when handling product.

Product Warranty

INNOTECH SELECT-ETCH is a proprietary product, warranted to be of uniform quality within our stringent manufacturing tolerances. As no control is exercised over the product use, no warranty is made as to the effects of such use (neither expressed or implied). Obligation of the seller and manufacturer under this warranty shall be limited to a refund of the purchase price of that portion of the material proven to be defective. The user assumes all other risk and liability resulting from uses of this product. Contact INNOTECH with any questions regarding this policy.

†PLEASE REFER TO CORRESPONDING TECHNICAL BULLETIN FOR PRODUCT AND APPLICATION DATA.

INNOTECH SELECT-ETCH and other INNOTECH products are for professional use only.

Innotech Decorative Concrete Products is a member of the ChromaScape® family of brands.
For more information, go to www.chromascape.com. ©2016 ChromaScape, Inc.

OM 09.16

INNOTECH products can be purchased at:



INNOTECH Decorative Concrete Products
2055 Enterprise Parkway • Twinsburg, OH 44087
Customer Service 877-829-7880 or 330-425-2506
Fax 330-425-2466
customerservice@innotechdcp.com
www.innotechdcp.com